

### Uncompromised Performance - Unequaled Versatility

The non-powered STX2 and STX2M Series loudspeakers unite advanced technology and application-driven engineering to bring live sound closer to the ultimate reference point: reality. Patented CoEntrant M/H transducers and unique innovations such as our Complex Conic horns combine to deliver natural sounding music and intelligible speech. Wherever audiences and operators demand superior performance and ease of use, STX2 and STX2M loudspeakers are an excellent choice for transparent, reference quality performance.

All STX and ST series loudspeakers are handcrafted especially for you in our Foothill Ranch, California facility. Numerous custom options are available.

### Applications

- Virtually any application where directional control and arrayability are critical issues and outstanding sonic performance is required.
- Distributed systems in sports arenas and stadiums.
- Multi-channel A/V playback systems, live sound and music systems in clubs and disco's (with optional subwoofers).
- Side fill in all types of large sound reinforcement systems.
- Array modules for theatrical and concert sound systems, sound reinforcement systems in Houses of Worship.



### Advanced Complex Conic Horns

Designed around the spherical expansion of the acoustic pressure wave, Complex Conic horns provide constant beamwidth/directivity without the problems associated with conventional rectangular horns. These unique waveguides eliminate low frequency pattern flip, an annoying characteristic of many horns. Their circular mouths have no corners to cause high frequency "feathering" and the resulting distortion. The results are audible: accurate pattern control, lower distortion and minimal coloration.

Designed around the spherical expansion of the acoustic pressure wave, Complex Conic horns provide constant beamwidth/directivity without the problems associated with conventional rectangular horns. These unique waveguides eliminate low frequency pattern flip, an annoying characteristic of many horns. Their circular mouths have no corners to cause high frequency "feathering" and the resulting distortion. The results are audible: accurate pattern control, lower distortion and minimal coloration.

### Patented CoEntrant Topology



The CoEntrant mid/high driver used in the STX2M integrates the acoustic output of an 8-inch mid-range cone and a 1-inch high frequency compression driver into a wideband, low-distortion, high-power true point source.

CoEntrant drivers loaded with Complex Conic horns offer numerous advantages over dual-horn and co-axial topologies, including smaller size, lower weight, inherent phase coherency and smoother frequency response.

## ST / STX Series

### STX2

### 12" Woofer - CoEntrant M/H Driver Complex Conic Horns



#### • Compact 3-Way Design, Outstanding Performance

Only 26.5" H x 14" W x 16 5/8" D, the STX2 delivers accurate full-range 50 Hz to 18 kHz high-level 131 dB Peak SPL performance.

#### • Three-Way Bi-Amplified Loudspeaker

Integral passive mid/high crossover for bi-amplification.

#### • Heavy-Duty 12-Inch Woofer

With treated fiber cone easily handles 500 Watts RMS of power.

#### • Exclusive Complex Conic Design

Provides constant beamwidth/directivity without the problems of conventional rectangular horns.

#### • Patented CoEntrant Topology

Integrates the acoustic output of an 8" cone and a 1" HF driver into a wideband, high power true point source.

#### • TRAP (True Array Principle) Design

STX2 loudspeakers can be easily turned into true 40° TRAP modules by rotating their horns 90 degrees. TRAP modules combine seamlessly to produce a phase aligned wave front virtually free of lobing.

#### • Choice of Coverage Patterns

Choose between tightly controlled 60° by 40° and 90° by 40° coverage patterns.

## TECHNICAL INFORMATION

### Sensitivity (1W/1m)

**Lows:** 95 dB  
**Mids:** 101 dB  
**Highs:** 109 dB

### Maximum SPL

**Lows:** 128 dB peak  
**Mids:** 129 dB peak  
**Highs:** 131 dB peak

### Dispersion

**STX2/64:** 60° H by 40° V  
**STX2/94:** 90° H by 40° V

**Freq. Resp:** 50 Hz to 18 kHz

**Mid/High Driver:** CDT-1L; SSD1802S-8B 1" HF (40W RMS) & SSL8-9 8" MF (150W RMS)

**LF Driver:** 12" model SSL12-13 woofer; 4" VC; 500 W RMS (1000 W program)

**Enclosure:** Multi-ply hardwood, perforated metal grille

**Crossover Points:** 600 Hz (passive 1500 Hz mid/high crossover is built-in)

**Power:** Lows: 500 Watts RMS @ 8 Ohms  
 Mid/Highs: 150 Watts RMS @ 8 Ohms

**Finish:** Black, white or custom paint. TuffTex, Natural (unfinished), Weather Resistant

**Connectors:** Neutrik 4-pin or screw terminals

**Hardware Options:** 12-point universal mtg hardware, Handles, Omnimount Series 60 nut-plates, Tripod Socket, AeroQuip Fly-track

**Dimensions** 26.5" H x 14" W x 16 5/8" D  
 (67.3 cm x 35.6 cm x 42.2 cm)

**Weight:** 75 Lbs. (34 Kg) net

## DIMENSIONAL INFORMATION

