



NOTES

1. Outside dimensions are for painted cabinets. Add approximately 0.25 inch for carpeted cabinets.
2. Attachment point locations are approximate. Design attachment plates with slotted holes for adjustability.

OMNIMOUNT SERIES 75 MOUNTING OPTION.

TRIPOD SOCKET OPTION.

PART NUMBER LIST			

REV	DESCRIPTION	DATE	BY
A	RELEASE -- ECO #2005	6/11/97	GL
B	4" WAS 4 1/4" O.M.D. ECO #2709.	4/7/99	
C	ADD 1/4 X 20 U-BRACKET MOUNTING 13/4 TYP. WAS 1 1/2 TYP. ECO #2737	6/7/99	
C	REVISED AND REDRAWN 4/5/98	6/7/99	

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCES ARE:		INTL	DATE	RENKUS-HEINZ, Inc.
DECIMALS	ANGLES	DRAWN P.R.	5/28/97	
.XX ± .125	± 2.5°	CHECK GL.	6/10/97	
		DESIGN ENG	6/10/97	
		APPROV		
		APPROV		
		REF DWG		
		D00508-C.DWG		
NEXT ASSY.	USED ON	DO NOT SCALE DRAWING		
APPLICATION	REARR AND REMOVE SHARP EDGES	SCALE 1 = 3	WEIGHT	

THE MATERIAL CONTAINED HEREIN IS PROPRIETARY TO RENKUS-HEINZ AND SHALL NOT BE REPRODUCED DISCLOSED OR USED FOR ANY OTHER PURPOSE WITHOUT THE WRITTEN APPROVAL OF RENKUS-HEINZ.

TITLE ASSEMBLY DWG, TRC81/9, TRC81/12 TRX81/9 & TRX81/12

SIZE	CODE	IDENT	DWG NO.	REV
D			600-SPKRASMTRC81	C